



Better Design

Easy to Install.
Corrosion
Protection.



Automatic Spring Brake Chamber

STROKE OPTION

2.5"
3.0"

SIZE OPTION

24-24 TO
30-30

4 YEAR
WARRANTY





Better Design | Easy to Install. Corrosion Protection.

TSE Brakes' Omni is a premium spring brake chamber engineered for dependable performance in demanding commercial vehicle applications. Designed with patented sealing technology, Omni delivers long service life, reliable performance, and straightforward installation.

Feature Highlights

- OEM preferred design
- Patented self-lubricating center seal
- Chrome silicon power spring
- Heavy-duty all-steel construction
- Full immersion e-coat protection
- Available in TL and TN configurations



Longer Service Life

- Patented sealing technology, premium internal components, and heavy-duty all-steel construction help reduce wear and extend brake chamber life in demanding operating environments.

Superior Corrosion Protection

- Every housing and internal component receives full immersion e-coating to provide complete corrosion protection—even in areas traditional coatings may not reach.

Fast, Easy Installation | Choose the configuration that fits your maintenance strategy :

TL Series

- Tamper-resistant sealed service side
- No external service clamp
- Reduced installation time

TN Series

- Traditional clamped service side
- Easy service replacement
- Familiar installation

Part Number	Category	Description	Dimension	Caged
3030TL2-2412	Direct Fit Units (Tamper Proof + Pre Cut Threaded Rod)	T-3030 2.5" stroke + long rod	9.75"	Y
3030TL2-4185	Direct Fit Units (Tamper Proof + Pre Cut Threaded Rod)	T-3030 2.5" stroke	5.75"	Y
3030TL3-2493	Direct Fit Units (Tamper Proof + Pre Cut Threaded Rod)	T-3030 3.0" stroke + long rod	9.75"	Y
3030TL3-3265	Direct Fit Units (Tamper Proof + Pre Cut Threaded Rod)	T-3030 3.0" stroke	5.75"	Y
3030TN2-C	Generic Will-Fit Units	T-3030 2.5" stroke + clevis	7.85"	N
3030TN3-C	Generic Will-Fit Units	T-3030 3.0" stroke + clevis	7.35"	N
3030TN2-HNTRX-C	Direct Fit Units (Clamped + Threaded Rod)	T-3030 2.5" stroke + long rod + clevis	9.75"	N
3030TN3-HNTRX-C	Direct Fit Units (Clamped + Threaded Rod)	T-3030 3.0" stroke + long rod + clevis	9.75"	N
3030TNW2-2998	Tandem with Welded Clevis for Truck & Trailer Application	T-3030 2.5" stroke + welded clevis	2.25"	Y



2310 Industrial Drive S.W. Cullman, Alabama 35055 | 256 736-6275
©2026 TSE Brakes, Inc. tsebrakes.com



Marmon
Transportation
Products
A Berkshire Hathaway Company