



**ENGINEERED FOR STRENGTH,  
LONGEVITY, AND RELIABLE  
PERFORMANCE**

**ultra life+**

Sizes available:  
2430, 3030 Std., Long stroke, 3036 Std. & Long stroke, 3036

## **PREMIUM SPRING BRAKES**

To Go Where No Spring Brake Has Gone Before

### **THE ULTRALIFE PLUS CHARACTERISTICS**

#### **Advanced Durability**

Designed to withstand the toughest environments, UltraLife Plus features the proprietary TSE All-N-One™ integrated pressure plate and diaphragm assembly, eliminating plate shifting and increasing the lifespan of the powerspring and diaphragm.

#### **Lightweight and Reliable**

Weighing one pound less than its predecessor, UltraLife Plus delivers superior strength, reduced vehicle weight, and improved durability for aftermarket replacements.

#### **Rigorous Testing**

Our extended durability testing simulates real-world operating conditions, virtually guaranteeing unmatched reliability under the most demanding environments and usage scenarios.

#### **Enhanced Safety and Maintenance**

TSE Sealed When It Counts™ technology seals out moisture and contaminants while driving, allowing ventilation when parked, offering superior protection and maintenance.

### **KEY BENEFITS FOR AFTERMARKET SUPPLIERS**

#### **Integrated Design**

All-in-one pressure plate and diaphragm assembly simplifies replacements and enhances reliability.

#### **Corrosion Protection**

Multi-layer coatings provide industry-leading resistance to harsh conditions.

#### **Long-Term Warranty**

Backed by up to 10 years for parts and corrosion resistance, offering peace of mind to fleet operators.

#### **Maintenance-Friendly**

Drain holes open when parked, allowing quick ventilation and improved serviceability.

# PERFORMANCE FEATURES

## TSE ULTRALIFE PLUS™ PREMIUM SPRING BRAKES



PART NUMBER	CATEGORY	DESCRIPTION	B DIMENSION	CAGED
3030TL2ULP-80026	Tandem with Clevis for Truck & Trailer Application	T-3030 2.5" stroke + clevis	5.75"	Y
3030TL2ULP-80031	Tandem with Clevis for Truck & Trailer Application	T-3030 2.5" stroke + long rod + clevis	9.75"	Y
3030TLW2ULP-80045	Direct Fit Units (Tamper Proof + Welded Clevis)	T-3030 2.5" stroke + welded clevis	6.80"	Y
3030TN2ULP-80049	Direct Fit Units (Clamped + Threaded Rod)	T-3030 2.5" stroke + clevis	5.75"	Y
3030TN2ULP-C	Generic Will-Fit Units	T-3030 2.5" stroke + clevis	7.85"	N
3030TN2ULP-HNTRX-C	Direct Fit Units (Clamped + Threaded Rod)	T-3030 2.5" stroke + long rod + clevis	9.75"	N
3030TL3ULP-80011	Tandem with Clevis for Truck & Trailer Application	T-3030 3.0" stroke + clevis	5.75"	Y
3030TL3ULP-80017	Tandem with Clevis for Truck & Trailer Application	T-3030 3.0" stroke + long rod + clevis	9.75"	Y
3030TLW3ULP-80036	Direct Fit Units (Tamper Proof + Welded Clevis)	T-3030 3" stroke + welded clevis	6.80"	Y
3030TN3ULP-80053	Direct Fit Units (Clamped + Threaded Rod)	T-3030 3.0" stroke + clevis	5.75"	Y
3030TN3ULP-C	Generic Will-Fit Units	T-3030 3.0" stroke + clevis	7.35"	N
3030TN3ULP-HNTRX-C	Direct Fit Units (Clamped + Threaded Rod)	T-3030 3.0" stroke + long rod + clevis	9.75"	N
3030TNW3ULP-80060	Tandem with Welded Clevis for Truck & Trailer Application	T-3030 3.0" stroke + welded clevis	2.25"	Y