



**OUT OF THE CHAMBER THINKING:
EASY TO INSTALL. EASY TO CLOCK**

ultralife+TM vct

TSE ULTRALIFE PLUS VCT

THE ULTRALIFE PLUS VCT CHARACTERISTICS

Simplified Installation

Designed with Variable Clocking Technology (VCT), UltraLife Plus VCT reduces installation time by up to 75%. The factory-sealed diaphragm ensures proper alignment, eliminating common installation errors.

Proven Performance

Every UltraLife Plus VCT unit undergoes rigorous testing, including vibration, pressure cycling, and salt spray tests, to guarantee performance you can trust.

Built for Durability

The unit's all-steel construction and advanced e-coating process provides an ultra superior corrosion protection from the elements, ensuring long-lasting reliability even in severe-duty environments.

Reduced Inventory Complexity

With only five part numbers covering most applications, the UltraLife Plus VCT streamlines inventory management and minimizes the need for excess stock.

KEY BENEFITS FOR AFTERMARKET SUPPLIERS

Versatile Design

Universal fit with 180° clock rotation eliminates the need for separate hand units.

Long-Term Warranty

Industry-leading coverage of up to 10 years ensures peace of mind for fleet operators.

Rapid Installation

Pre-assembled, factory-sealed units reduce labor time and training requirements.

Corrosion Resistance

Multi-stage e-coating protects against rust and wear for extended service life.

PERFORMANCE FEATURES

TSE ULTRALIFE PLUS™ VCT PREMIUM SPRING BRAKES



PART NUMBER	CATEGORY	DESCRIPTION	B DIMENSION	CAGED
3030SV2ULPK	VCT - Variable Clocking Technology Piggyback Kits	VCT T-3030 2.5" stroke single Kit + Box	-	Y
3030SV3ULPK	VCT - Variable Clocking Technology Piggyback Kits	VCT T-3030 3.0" stroke single Kit + Box	-	Y
3030TV2ULP-HNTRX	VCT - Variable Clocking Technology Direct Fit (Clamped + Threaded Rod)	VCT T-3030 2.5" stroke + long rod	9.75"	Y
3030TV3ULP-HNTRX	VCT - Variable Clocking Technology Direct Fit (Clamped + Threaded Rod)	VCT T-3030 3.0" stroke + long rod	9.75"	Y
3030TVW3ULP-80085	VCT - Tandem with Welded Clevis for Truck Applications	VCT T-3030 3" stroke + welded clevis	2.25"	Y
3036TVW3ULP-80114	VCT - Tandem with Welded Clevis for Truck Applications	T-3036 3" stroke + welded clevis	2.25"	N