



Type 36 Brake Chambers

ultra life+TM



THE ULTRALIFE PLUS CHARACTERISTICS

New Urethane Coating

New urethane powder coating applied over our proven 8-step e-coat base provides industry leading long-term resistance to humidity and corrosion

Proprietary TSE Seal

Proprietary TSE Sealed When It CountsTM utilizes air pressure in chamber to push the diaphragm against the housing drain holes to create a secure seal against moisture and contaminants while driving. When parked, drain holes open up to allow draining and ventilation.

TSE All-N-OneTM

Proprietary TSE All-N-OneTM integrated pressure plate and diaphragm assembly eliminating plate shifting, increasing power spring and diaphragm life

Patented bushing

Patented bushing, prepacked with low temperature synthetic grease, provides a seal that reduces center section leaks and brake drag

Dust cap pressure relief valve

Dust cap has pressure relief feature to prevent back pressure or vacuum in spring compartment

New Urethane Spring Coating

New urethane powder coating applied over our proven 8-step e-coat base for the ultimate spring corrosion protection.

TSE High Vibration mounting base

TSE designed High Vibration "HV" mounting base reduces vibration for longer life

Optional fixed position clevis

Optional fixed-position clevis with stainless steel pins maximizes corrosion protection and helps reduce seized pins and bent push rods

TYPE 36 ULTRALIFE PLUS BRAKE CHAMBERS



PART NUMBER	CATEGORY	DESCRIPTION	B DIMENSION	CAGED
3036TL3ULP-80101	Generic Will-Fit Units	T-3036 3.0" stroke	1.50"	N
3036TN2ULP-80103	Generic Will-Fit Units	T-3036 2.0" stroke + clevis	2.0"	N
3036TN2ULP-C	Generic Will-Fit Units	T-3036 2.0" stroke + clevis	7.8"	N
3036TN3ULP-C	Generic Will-Fit Units	T-3036 3.0" stroke + clevis	7.3"	N
3636TN3ULP-C	Generic Will-Fit Units	T-3636 3.0" stroke + clevis	7.25"	N