

TSE BRAKES INC. PART DESCRIPTION

NOTE - Customer-specified Part Number can be different from TSE Description

ELEMENTS OF THE TSE PART DESCRIPTION								
U.S. Size service	U.S. Size parking	ТҮРЕ	STYLE			PUSHROD STYLE	STROKE mm = METRIC	PRODUCT LINE
20	24	T	L			D	64	Н
\downarrow	4	\downarrow	↓ ↓			\downarrow	\downarrow	\downarrow
Defines Type of Service Chamber	Defines Type of Parking Chamber	Defines as Simple Tandem or Service Chamber	Defines Style/Make of Unit			Defines Application : Disc Brake or S-Cam?	Specifies Stroke of unit	Additionnal Features otherwise leave blank
			· L					
\checkmark	\checkmark	•	Service	Parking	Center Section	•	\downarrow	\downarrow
Sizes available : 04 ¹ 09 ² 12 14 16 18 20	Sizes available : Blank = SC 16 ³ 24 30 36 ⁴	S = Single T = Tandem SC = Service Chamber DC = Double serv Chamber PK = Pinlock P = Piston	S = Sealed N = Clamped V = VCT Z = Sealed Y = Clamped M = Clamped B = Clamped	Sealed Sealed RPSealed RPSealed Clamped Sealed Clamped	Steel Steel Steel Steel Steel Alum Alum	Blank = threaded P/R D = Disc P/R R = Removable P/R X = Pinlock W = Fixed Clevis V = Wedge P/R (R = TSE-REX P/R)	Metric Ports Metric Mounting Bolts 45mm¹ 51mm¹ 57mm 64/65mm 75/76mm	Blank = OMNI or standard ULP = Ultra Life Plus H = HOT (Piston Performance) HULP = HOT Ultra Life Plus R = Remote K = Add Diaphragm & Clamps DX = Disc - Welded Clevis F = HD Spring Force
22 24 27 30 32 36 NOTES ¹ Pinlock Only ² SC and Wedge Br	24 (VCI = Variable Clocking lechnology) 27 30 32 36 S KEY ck Only Greyed out options are obsolete or discontinued							 P = (Plus) Non Contact Spring UL = Ultra-Life IM = Ultra-Life for Intermodal OE = Ultra-Life for OEMs A = Alumiline



³ Wedge Brake Only ⁴ Available in UL Plus Only

> 2310 Industrial Drive S.W. Cullman, AL, US 35055

WWW.TSEBRAKES.COM 1 256 736-6275